



Features

- Proven ALPR technology now available in a hand held portable configuration
- Ideal for parking violation enforcement, parking facility inventory and a variety of police applications
- Greater efficiency and throughput over manual data input solutions
- High resolution sensor optimized for true day or night License Plate Recognition
- Models available for high-speed and distance applications
- Provides up to 60 progressive scan images per second

The LY family of portable license plate capture imaging systems brings the technology of Automated License Plate Recognition (ALPR) systems to a mobile application platform.

These new purpose-engineered imaging devices address the needs of parking, law enforcement and facilities management. Most current solutions require a manual entry of license plate information; a process that is slow and error prone. With the introduction of the LY imaging device there is a solution which allows license plate information to be read and recorded as you drive past a vehicle, or when a vehicle drives past you, with the added benefit of a visual record of every plate read by the system.

INEX/ZAMIR has applied the technology advancements of the HY high speed imaging device to the new LY family to create a high performance and yet very portable unit that delivers quality images necessary for high accuracy ALPR. Every LY unit employs an integral infrared LED light source thereby eliminating the need for any supplemental lighting. Models have been engineered for different tasks, and will provide effective operation at varying distances from imager to target

General

Maximum operating range----- 50 feet (15 meters)
 Vehicle speed range ----- < 100 MPH (160 KPH)

Operation

Illumination ----- Fixed array of 48 IR LEDs.
 Minimum Operating Luminance----- 0 Lux
 Shutter----- User selectable multi-shutter, up to 3 settings 1/2000 to 1/100,000 secs
 Video Output Level ----- 1.0Vp-p, 75 Ohms

Imager

Scanning System ----- EIA: >525 TV lines (H), 60 frames/sec,
 CCIR: >550 TV lines (H), 50 frames/sec
 Image Device ----- Interline transfer CCD
 Image Sensor----- 1/3"

Electrical

DC Voltage ----- 12 VDC +/- 10%, Class 2 low-voltage
 Power Consumption----- 24 Watts

Mechanical

Lens Mount----- CS Mount (16 mm lens provided)
 Dimensions (W x H x D)----- 3.8in x 3.8in x 10.9in (96mm x 96mm x 210mm)
 Unit Weight ----- 4 lbs (1.8 Kg)
 Housing Construction and Finish----- Powder coated aluminum
 Cable Entry----- Rear of camera
 Mount ----- Mounting rail with removable grip

Environmental

Operating Temperature ----- -4 F to 122 F (-20 C to 50 C)
 Storage Temperature ----- -40 F to 152 F (-40 C to 70 C)
 Humidity ----- 0% to 85% non-condensing
 Protection Level ----- IP65

Regulatory

Emissions----- FCC Part 15 Class B, CE, Class B
 Product Safety----- CE
 Eye Safety ----- Class 1 LED Product

Connectors and Cables

Input Connector to LY----- Quick connect screw on connector for power and video
 Cable----- 6' integrated coiled power and video cable
 Video Connection at Computer----- USB
 Power Connection----- "Cigarette Lighter" style connector

Data subject to change without notice

